

# TORQUE

Proper torque (or tightening) depends on many factors including: surface texture, finish, and lubrication. These values are only a guideline.

## CAP SCREWS

DIAMETER COARSE	GRADE 2		GRADE 5		GRADE 8	
	DRY FT/LBS	LUB FT/LBS	DRY FT/LBS	LUB FT/LBS	DRY FT/LBS	LUB FT/LBS
1/4-20	5.5	4.2	8	6.3	12	9
5/16-18	11	8	17	13	24	18
3/8-16	20	15	30	23	45	35
7/16-14	32	24	50	35	70	50
1/2-13	50	35	75	55	110	80
9/16-12	70	55	110	80	150	110
5/8-11	100	75	150	110	210	160
3/4-10	175	130	260	200	390	280
7/8-9	170	125	430	320	600	450
1-8	250	190	640	480	910	680

DIAMETER COARSE	18-8 SS	316 SS	BRASS
	INCH/ LBS	INCH/LBS	INCH/LBS
1/4-20	75.2	78.8	61.5
5/16-18	132	138	107
3/8-16	236	247	192
7/16-14	376	393	317
1/2-13	517	542	422
9/16-12	682	713	558
5/8-11	1110	1160	907
3/4-10	1530	1582	1249
7/8-9	2328	2430	1905
1-8	3440	3595	2815

DIAMETER FINE	GRADE 2		GRADE 5		GRADE 8	
	DRY FT/LBS	LUB FT/LBS	DRY FT/LBS	LUB FT/LBS	DRY FT/LBS	LUB FT/LBS
1/4-28	6.3	4.7	10	7.2	14	10
5/16-24	12	9	19	14	27	20
3/8-24	23	17	35	25	50	35
7/16-20	36	27	55	40	80	60
1/2-20	55	40	85	65	120	90
9/16-18	80	60	120	90	170	130
5/8-18	110	85	170	130	240	180
3/4-16	200	140	300	220	420	310
7/8-14	180	140	470	350	670	500
1-14	280	210	720	540	1020	760

DIAMETER COARSE	18-8 SS	316 SS	BRASS
	INCH/ LBS	INCH/LBS	INCH/LBS
1/4-28	94	99	77
5/16-24	142	147	116
3/8-24	259	271	212
7/16-20	400	418	327
1/2-20	541	565	443
9/16-18	752	787	615
5/8-18	1244	1301	1016
3/4-16	1490	1558	1220
7/8-14	2318	2420	1895
1-14	3110	3250	2545

## ALLOY SOCKET PRODUCTS

SOCKET CAP SCREWS			FLAT HEAD		BUTTON HEAD		LOW HEAD	SHOULDER SCREWS
NOMINAL SIZE	TORQUE FT/LBS		TORQUE INCH LBS		TORQUE INCH LBS		TORQUE INCH LBS	TORQUE INCH LBS
	COARSE	FINE	COARSE	FINE	COARSE	FINE	COARSE	COARSE
1/4	17	19	100	110	100	110	78	50
5/16	35	38	200	220	200	220	156	125
3/8	62	70	350	400	350	400	273	265
7/16	100	109	560	625	--	--	--	--
1/2	1510	172	850	1000	850	1000	615	470
5/8	283	317	1700	1900	1700	1800	1315	1150
3/4	500	562	3000	3200	--	--	--	2000
7/8	688	767	5000	5400	--	--	--	--
1	1040	1080	8000	7600	--	--	--	4000



2531 E. Jensen Ave, Fresno, CA 93706 | P: 559-485-8658, F: 559-485-8674, E: info@frontierfastener.com

www.frontierfastener.com

Frontier Fastener makes no warranties as to the accuracy, completeness and reliability of the information on this page. Use of the information is strictly at your own risk and Frontier Fastener will not be liable for any losses and/or damages.